



STROMVERSORGUNG/POWER SUPPLY	380-415V 3N~ 50-60Hz
M = ANSCHLUSSKLEMME/TERMINAL CLAMP	FV122 6 POLI - 40 A - 450 V
B1 = SCHALTER/SWITCH	EGO 49.41015.300 4 Poli 16A 250V T150 55.32532.805
S1 = SICHERHEITSTHERM./SAFETY THERM.	T=160°C -17K 16A 55.32524.160 T=135°C -12K 16A
T1 = THERMOSTAT/THERMOSTAT	EGO 55.34014.190 16A 400V [30°C-90°C]
LV = KONTROLLAME GRÜN/GREEN IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LR = KONTROLLAME ROT/RED IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
LB = KONTROLLAME WEIß/WHITE IND. LIGHT	SIGNAL LUX Mod 21.3 230V (T120) Silicon Leads
R1,R2,R3 = HEIZKÖRPER/HEATING ELEMENT	3500 watt 230V 15.2A
WAHRSCHALTER/TASTER/SELECTOR	SXL4 427H110000 230V 16A FASTON 4.8
VENTIL WASSERBEFÜLLUNG/ VALVE WATER LOAD	
KABEL/CABLE	CAVO H05SJ-K Section 2.5 / 4 mmq Section 1.5 mmq
KABEL Z. VENTIL/ CABLE F. VALVE	CAVO H05SJ-K Section 1 mmq
KABEL F. KONTROLLAMPE/CABLE F. IND. LIGHT	CAVO H05SJ-K Section 0.75 mmq